

1

2

3

4

1

2

3

4

1

2

3

4

1

2

3

4

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

D

C

B


A

REFER DRAWING:- 007537394C91

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989 (DIMENSION)										SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA					
LINEAR IN mm.		OVER	0.5	3	6	30	120	400	1000	2000	WELDING SYMBOLS:IS813					REMOVE ALL SHARP CORNERS & BURRS	
		UPTO	3	6	30	120	400	1000	2000	4000							
f	FINE (X.XXX)		±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	-	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0		NAME	DATE	PROJECT CODE:	
m	MEDIUM (X.XX)		±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2		<CC> COUNT : 0		DSNR	AR	07-06-2023	ER NUMBER:ER23C0000228
c	COARSE (X.X)		±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4		WEIGHT(kg) : 0.03		CHKR	NVC	07-06-2023	DESCRIPTION :
v	VERY COARSE (X)		±0.5	±1	±1.5	±2.5	±4	±6	±8			S/F AREA(cm²): 13		APPR	DS	07-06-2023	PIN STOPPER
ANGULAR IN deg.		LENGTH OF SHORTER SIDE OF THE ANGLE IN mm.															
		OVER	-	10	50	120	400										
		UPTO	10	50	120	400	-										
f	FINE (X.XXX)		±1°	±0°30'	±0°20'	±0°10'	±0°5'										
m	MEDIUM (X.XX)		±1°30'	±1°	±0°30'	±0°15'	±0°10'										
c	COARSE (X.X)		±1°30'	±1°	±0°30'	±0°15'	±0°10'										
v	VERY COARSE (X)		±3°	±2°	±1°	±0°30'	±0°20'										

DO NOT SCALE
ALL DIMENSIONS ARE IN mm



DWG.SIZE : A4

PART NUMBER :
008032668U01

CL:
NA

SCALE : 2:1

SHEET: 1 OF 1

CHECK DRAWING WITH LATEST CHANGE No

DO NOT CHANGE MANUALLY

COMPUTER GENERATED DRAWING

4